



Introducing the
WORKBOSS® CT
Non-Directional Compact Tractor Tire

The WorkBoss® CT sets a new standard for compact tractor performance. Designed by OTR from the ground up, every detail of the tread, sidewall, and profile is engineered with purpose — delivering a quieter ride, greater stability under load, and improved durability and handling. With industry-leading ply ratings, operators and OEMs can match the right tire to the right machine, and gain confidence in both everyday use and heavy-duty applications.

***Making Customers'
Lives Easier®***



Squarer sidewall profile:
Increased durability,
reduced sidewall flex



Continuous lug design:
Added stability under
heavy loads

Shallower grooves:
Stiffer tread that
resists bending

Tie bars between tread blocks:
Improves handling confidence

WORKBOSS® CT

NON-DIRECTIONAL
COMPACT TRACTOR TIRE

KEY FEATURES:

- **Quieter, smoother ride:** Optimized tread pattern reduces noise and vibration
- **Extended life:** Advanced rubber compounds resist premature wear
- **Multiple ply ratings per size:** Options for different machines and HP ranges, with select ply ratings higher than industry standards
- **Integrated QR code:** Instant access to specs, support, and product info

Tire Size	Ply*	Rated Pressure	Overall Diameter	Section Width	Rim Size	Load Capacity	Static Loaded Radius	Rolling Circumference	Part Number
		PSI (KPA)	IN (MM)	IN (MM)	IN	LBS (KG)	MM	MM	
16x7.50-8	6	38 (260)	16.0 (406)	7.4 (188)	8X5.50	785 (355)	186	1,168	T-104035
18x8.50-10	8	46 (320)	17.8 (452)	8.3 (211)	10X7.00 AT	1,140 (515)	209	1,314	T-103851
23x8.50-12	6	36 (250)	22.8 (578)	8.4 (214)	12X7.00 JA	1,520 (690)	266	1,670	T-103227
24x12.00-12	6	32 (220)	24.0 (610)	12.0 (305)	12X10.50	2,040 (925)	279	1,753	T-104012
25x8.50-14	6	36 (250)	25.2 (640)	8.2 (208)	14X7.00	1,610 (730)	296	1,859	T-104046
26x12.00-12	8	42 (290)	26.0 (660)	11.9 (302)	12X10.50 AT	2,705 (1,215)	300	1,884	T-103817
27x8.50-15	8	44 (300)	26.9 (683)	8.6 (218)	15X7.00	2,150 (975)	316	1,984	T-104051
10-16.5	6	30 (210)	30.5 (775)	10.2 (259)	16.5X8.25	2,270 (1,030)	357	2,245	T-104001
12-16.5	6	42 (290)	32.7 (831)	12.1 (307)	16.5X9.75	4,180 (1,900)	380	2,391	T-103236
14-17.5	6	32 (220)	36.3 (922)	13.7 (348)	17.5X10.50	4,800 (2,180)	420	2,639	T-103239
14.9-24	8	30 (210)	49.3 (1,252)	15.1 (384)	24XW12	6,950 (3,150)	572	3,593	T-104057
15-19.5	6	30 (210)	40.3 (1,024)	15.3 (389)	19.5X11.75	4,180 (1,900)	467	2,932	T-104052
43x16.00-20	6	30 (210)	43.1 (1,095)	15.9 (404)	20XW13L	5,680 (2,575)	498	3,127	T-104056
16.9-24	6	30 (210)	51.7 (1,313)	17.0 (432)	24XW13L	8,250 (3,750)	597	3,749	T-104067

*Additional ply ratings available upon request.



Want the WorkBoss® CT
to work for you?

800-833-6309
otrwheel.com/product/workboss-ct

WorkBoss®
AN OTR BRAND